


Ventilacijske tipke

vent buttons

LT 43U / SLT 42 / LT 41A



LT 43U-W



LT 41A



SLT 42A-SD



LT 43U



LT 43U-SD



SLT 42U

24 VDC

Informacije o proizvodu

- LT 43U - ventilacijska tipka podometna na vojo tudi v kombinaciji z avtomatskimi stikali
- SLT 42 - ventilacijska tipka na ključ podometna ali nadometna
- LT 41A - ventilacijska tipka nadometna za montažo zunaj

Product Information

- LT 43U - flush mounted vent button also as combination with automatic switches
- SLT 42 - key-operated vent button surface or flush mounted design
- LT 41A - surface vent button in moistureproof design

Funkcije in delovanje

LT 43U:

- ventilacijska tipka za montažo v podometno razvodno dozo
- funkcije: Odpiranje-Stop-Zapiranje s pritiskom na obe tipki hkrati
- barva: bela
- LT 43U-W kombinirana dvojna tipka, z vstavljenim avtomatskim vremensko/temperaturnim stikalom, On-Off
- LT 43U-SD dodatno z vstavljenim LED-indikacijo za Odprto stanje
- montaža v razvodno dozo 55 mm ali dvojno razvodno dozo, (dobava brez zazvodne doze)

SLT 42:

- ventilacijska tipka na ključ, za montažo v podometno razvodno dozo, cilindrična ključavnica
- funkcije: On-Off (zadržana pozicija) na ključ
- barva: barva
- SLT 42U-SD dodatno z vstavljenim LED-indikacijo za Odprto stanje
- montaža v globoko razvodno dozo 55 mm UP-Dose, razvodna doza in cilindrična ključavnica niso vključeni v dobavo

SLT 42A:

- ventilacijska tipka na ključ, montaža nadometna za profilno cilindrično ključavnico
- funkcije: Odpiranje-Zapiranje (zadržana pozicija) na ključ
- zaščita: IP 54, barva: svetlo siva
- SLT 42A-SD v nadaljevanju z LED-indikacijo za Odprto stanje
- cilindrična ključavnica ni vključena v dobavo

LT 41A

- ventilacijska tipka, nadometni dizajn za vgradnjo zunaj
- funkcije: Odpiranje-Stop-Zapiranje
- zaščita: IP 55, barva: svetlo siva

Features

LT 43U:

- vent button in flush mounted design
- functions: Open-Stop-Closed via double button with non-interlocked NOC's
- colour white
- LT 43U-W as twofold combination, in addition with weather / temperature automatic switch, On-Off
- LT 43U-SD in addition with integrated LED-visual display Open
- mounted in 55 mm flush socket or two combined flush sockets, (not included in extent of supply)

SLT 42:

- key-operated vent button in flush mounted design for profile semicylinder
- functions On-Off (storage operation) via key-operated single-pole change-over contact
- colour white
- SLT 42U-SD in addition with integrated LED-visual display Open
- mounted in recessed 55 mm flush socket, flush socket and semicylinder not included in extent of supply

SLT 42A:






- key-operated vent button in surface moistureproof design for profile semicylinder
- functions: Open-Closed (storage operation) via key-operated single-pole change-over contact
- protective system: IP 54, colour light grey
- SLT 42A-SD in addition with integrated LED-visual display Open
- profile semicylinder not included in extent of supply

LT 41A

- vent button in surface design for damp areas
- function: Open-Stop-Closed via double button with non-interlocked NOC's
- Protective system: IP 55, Colour: light grey

Obseg produktov

Range of products



Tip	Art.-Nr.	BxH(x T)/mm	Teža/kg	Pripombe
Type	Ord.-No.	WxH(x D)/mm	Weight/kg	Comment
LT 43U	30.400.90	80 x 80	0,15	
LT 43U-SD	30.400.20	80 x 80	0,15	z LED-display with LED display
LT 43U-W	30.400.70	150 x 80	0,30	eno avtomatsko stikalo one automatic switch
SLT 42U	30.401.10	80 x 80	0,15	
SLT 42U-SD	30.400.50	80 x 80	0,15	z LED-display with LED display
SLT 42A	30.400.30	70 x 90 x 65	0,45	
SLT 42A-SD	30.400.40	70 x 90 x 65	0,45	z LED-display with LED display
LT 41A	30.400.00	70 x 70 x 45	0,20	

Tip	Art.-Nr.	Teža/kg	B x H x T/mm	Pripombe
Type	Ord.-No.	Weight/kg	W x H x D/mm	Comment
AP-LT	70.600.16	0,10	80 x 80 x 35	nadometni, enojni socket, surface mounted, single
AP2-LT	63.600.02	0,20	150 x 80 x 35	nadometni, dvojni socket, surface mounted, double
PHZ 28	70.600.53	0,15		cilindrična ključavnica, vklj. 2 ključena za SLT profile semicylinder lock, incl. 2 keys for SLT

Pridržujemo si pravico do tehničnih sprememb.
Rights to technical modifications reserved.

© 2012 D+H Mechatronic, Ammersbek



ZIP Inzeniring d. o. o. Tolmin
tel./ faks: + 386 (0) 5 38 49 009
GSM: + 386 (0) 41 61 83 80
www.zip-inzeniring.si / info@zip-inzeniring.si
Pooblaščen D+H Mechatronic prodajno - servisni partner.